

Your partner in inspection and quality control



checkweigher

08D3





checkweigher

08D3

Equipment

- Digital electronics with alphanumeric graphic display
- Electronic self-calibration device
- Production data management in conformity with the standards in force
- 3 levels password access protection
- Speed adjustable from keypad
- Mobile average function
- 100 storable product programs
- 2 RS232 serial ports
- Conformity with standards ISO-FDA HACCP

Accessories

- Ejection systems
- Reject management systems
- Wind-prevention tunnel
- 24-columns panel printer
- Fast disassembly conveyors (220 mm)
- Products programs memory expansion
- USB interface
- Ethernet interface
- Feed-back function
- Lamp to signal alarms



Technical Specifications

08D3

MID compatible

Weighing range	from 0 up to 2600 g	from 100 up to 1600 g
Display division	from 0,5 g	from 1,0 g
Linear speed	up to 100 m/min	up to 75 m/min
Throughput	up to 300 ppm	up to 250 ppm
Accuracy*	from $\pm 0,5$ g	from $\pm 0,5$ g
Pneumatic supply	0,6 Mpa	0,6 Mpa
Air consumption (for ejection)	1 NL	1 NL
Power supply	230V 50/60Hz single phase	230V 50/60Hz single phase
Power consumption	700 W	700 W
Mirror finishing of metal parts	Stainless steel IP65	Stainless steel IP65

*depending on the weight, dimensions and type of product



Plates configurations

Infeed A	Weighing B	Outfeed C
400	400	400
500	300	400
300	500	500

